

Special types

The full range of special types is available on request.

A selection is presented below.

Section	Type	Description
	OS-A13	Elastomer outer diameter, sealing lip without spring + protective lip
	OS-C12	Metal outer diameter +reinforcing cap, sealing lip without spring
	OS-C13	Metal outer diameter +reinforcing cap, sealing lip without spring + protective lip
	OS-D10	Elastomer outer diameter, 2 sealing lips spring-loaded, for separation of two media
	OS-D15	Metal outer diameter, 2 sealing lips spring-loaded, for separation of two media
	OS-G10	Elastomer outer diameter, ribbed, spring loaded sealing lip
	OS-G11	Elastomer outer diameter, ribbed, spring loaded sealing lip + protective lip
	OS-G13	Elastomer outer diameter, ribbed, sealing lip without spring + protective lip

Section	Type	Description
	OS-N34	Elastomer outer diameter, spring loaded sealing lip, pressure loadable (see operating parameters/pressure)
	OS-Q18	Outside sealing, spring loaded sealing lip, inside diameter elastomer coated
	OS-Q10	Outer diameter fabric-reinforced, spring loaded sealing lip
	OS-Q11	Outer diameter fabric-reinforced, spring loaded sealing lip + protective lip
	OS-Q12	Outer diameter fabric-reinforced, spring loaded sealing lip, radial lubricating grooves on the bottom side
	OS-Q13	Outer diameter fabric-reinforced, spring loaded sealing lip, radial lubricating grooves on the bottom side + circumferential groove in the outer diameter
	OS-BG10	Outer diameter half metal, half elastomer, ribbed, spring loaded sealing lip
	OS-BG11	Outer diameter half metal, half elastomer, ribbed, spring loaded sealing lip + protective lip

Section	Type	Description
	OS-PA30	Non-mould processing, metal outer diameter, PTFE sealing lip without spring
	OS-PA31	Non-mould processing, metal outer diameter, PTFE sealing lip without spring
	OS-PA32	Non-mould processing, metal outer diameter, PTFE sealing lip without spring
	OS-ST18	Cassette seal
	OS-W10	Non-mould processing, metal outer diameter, spring loaded sealing lip
	OS-W11	Non-mould processing, metal outer diameter, spring loaded sealing lip + protective lip
	OS-W50	Non-mould processing, turned PTFE seal + O-ring on outer diameter, spring loaded sealing lip