


## OS-G12



### Description

- Elastomer-coated OD, ribbed
- Non-spring-loaded sealing lip

### Special features

- Non-spring-loaded lip design, for secondary sealing jobs e.g., grease sealing
- Low friction
- Compact design
- Little installation space
- Reliable static sealing inside housing
- For housings with high thermal expansion, e.g., light metal housing
- For split housings
- For housings with increased surface roughness
- No risk of fretting corrosion

### Applications e.g.:

Secondary sealing jobs

- Mechanical and apparatus engineering
- Drive systems
- Electric motors

### Materials

#### Standard material

Elastomer	NBR 70 green
Metal case	Carbon steel according to DIN EN 10139

### Special materials

Elastomer	FKM
	Silicon
	ACM
	HNBR
	CR
	EPDM
Metal case	Stainless steel 1.4301

### Application parameters

For the standard materials combination:

Temperature	-40°C to +100°C
Pressure	depressurized
Shaft speed	max. 6 m/s, and acc. to chart „Operating parameters for rotary shaft seals“
Media	Mineral oil based lubricants, synthetic lubricants

When synthetic lubricants are used for which there is no empirical experience, test the compatibility in the laboratory or - better even - in practical trials. The operating temperature should not exceed 80°C.

### Design information

#### Shaft

Tolerance	ISO h11
Hardness	min. 45 HRC
Roughness	$R_a = 0.2 - 0.8 \mu\text{m}$ $R_z = 1 - 5 \mu\text{m}$ $R_{\text{max}} \leq 6.3 \mu\text{m}$
Surface finish	free of orientation (lead free)

#### Housing bore

Tolerance	ISO H8
Roughness	$R_a = 1.6 - 6.3 \mu\text{m}$ $R_z = 10 - 20 \mu\text{m}$ $R_{\text{max}} \leq 25 \mu\text{m}$

### Installation

Please read our installation instructions.